

DATA RECONSTRUCTION METHOD AND SYSTEM EMPLOYING THE SAME

866260-4429T60

1 BACKGROUND OF THE INVENTION

The present invention relates to a memory for performing access or read/write in parallel with a plurality of independent storage units as a set, and more particularly to a data reconstruction system and a method used therein which are available in occurrence of a failure.

The technology for controlling discs arranged in parallel is disclosed in JP-A-H1-250128 corresponds to U.S. Patent Application Serial No. 118,785 filed on November 6, 1987 and JP-A-H2-135555.

As for the technology for achieving the large capacity of a memory and the high speed transfer of data, there is known a method in which the data is striped into a plurality of data of bit unit, byte unit or arbitrary unit, with a plurality of storage units as a set, to be stored in the respective storage units, and when the data is to be read out, the plurality of data is simultaneously read out from the respective storage units. Moreover, in this method, the data to be used for a parity check is produced from the data striped up among the storage units to be stored in another storage unit. When the failure occurs in any of the storage units, the data stored in the remaining normal storage units and the data for the parity check are used to

1 reconstruct the faulty data, thereby to improve the
reliability of the memory.

Further, there is known the technology in
which when the failure occurs in any of the storage
5 units, not only the data is reconstructed for the normal
read operation, but also the data stored in the storage
unit at fault is reconstructed to be stored in the
normal storage unit which is additionally provided.
With this technology, the reconstructed data is stored
10 in the spare storage unit and the data is read out from
the spare storage unit for the subsequent access,
whereby it is possible to improve the availability of
the memory.

The failure of a certain number of storage
15 units can be repaired by providing the parity data, and
the data can also be reconstructed by the provision of
the spare storage unit. However, for the operation of
repairing the failure, it is necessary to read out all
of the data stored in the normal storage units and the
20 data for the parity check, reconstruct the faulty data
and write the reconstructed data to the spare storage
unit. Therefore, during the repair of the failure, the
storage units are occupied so that the request to
process the normal access or read/write which is issued
25 from a host unit continues to wait. This results in the
degradation of the performance of the memory. As for
the error check method for reconstructing the faulty

1 data, there are known the parity data, the Reed-Solomon
Code and the error check code (ECC).

Although the redundancy is provided for the
failure of a plurality of storage units, the failure
5 repair in the failure of one storage unit and that in
the failure of a plurality of storage units are managed
without taking the distinction therebetween into
consideration. Therefore, putting emphasis on the
repair of the failure, since the processing of the
10 normal access or read/write cannot be performed inspite
of the failure of one storage unit, there arises a
problem in that the efficiency of the processing of the
normal access or read/write is reduced. On the other
hand, putting emphasis on the normal access or
15 read/write operation, there arises a problem in that the
time required for the repair of the failure is not
secure during the failure of a plurality of storage
units, and as a result, the possibility that the whole
system may break down will be increased.

20 SUMMARY OF THE INVENTION

It is therefore an object of the present
invention to minimize the reduction of the processing of
the normal access or read/write in the failure, limit
the time required for the repair of the failure within a
25 fixed period of time, and ensure the high reliability,
with respect to a memory which has the redundancy for
the failure of two or more storage units.

09162444-092998

1 It is another object of the present invention
to provide a data reconstruction system which is capable
of selecting a suitable data reconstruction method in
correspondence to the various kinds of conditions
5 relating to the repair of the failure and carrying out
the most suitable data reconstruction processing.

 It is still another object of the present
invention to provide a control system which is capable
of changing the procedure of data reconstruction
10 processing in correspondence to the change of redundancy
relating to the number of ECC discs included in a
plurality of storage units which are arranged in
parallel to one another.

 The above objects of the present invention are
15 attained by the provision of a memory comprising: a
group of storage units for striping data into a
plurality of data of bit unit, bite unit or arbitrary
unit to store therein the striped data, the plurality of
independent storage units forming a set; discs for
20 storing therein ECC data corresponding to the striped
data; a spare storage unit for storing therein the
reconstructed data; an I/O-reconstruction control
circuit for receiving a command relating to I/O issued
from a host unit to execute processing in accordance
25 with the command or respond to the host unit; a timer
for giving the point of failure, an elapsed time during
the data reconstruction, a unit time and the like; a
data reconstructing table for the storage unit at fault;

09162444 "0929999

1 and a faulty data reconstructing circuit for performing
discovery of the faulty data, data reconstruction and an
operation of writing data to a spare storage disc,
wherein when a failure occurs in any of the storage
5 units, the faulty data reconstructing circuit detects
the failure by an error check to inform the I/O-
reconstruction control circuit of the failure, and the
I/O-reconstruction control circuit discriminates a state
of the failure to select the preferred processing
10 suitable for the state of the failure out of the
processing of the normal access or read/write and the
data reconstruction processing, thereby to execute the
selected processing, or set the frequency of the
processing of the normal access or read/write and the
15 data reconstruction, or the ratio of the processing
amount.

When the failure occurs in the above memory,
the redundancy of the memory, the elapsed time during
the data reconstruction, and the state of the normal
20 access or read/write processing and the like are
discriminated, and the data reconstruction processing
(method) suitable therefor is selected. Therefore, it
is possible to prevent reduction of the performance of
the processing of the normal access or read/write and
25 ensure the high reliability of the memory. More
specifically, in the case where the number of storage
units at fault has a room for the redundancy of the
memory, there is selected the data reconstruction

09162444.092998
866260.4429160

1 processing (method) in which the processing of the
normal access or read/write is given preference, and the
faulty data is reconstructed within the remaining period
of time. Therefore, no load is put on the processing of
5 the normal access or read/write. On the other hand, in
the case where there is no room in the redundancy, since
the processing of reconstructing faulty data is given
preference, it is possible to ensure the reliability for
the failure of the memory. Moreover, in the case where
10 there is a room in the redundancy, since the data
reconstruction processing (method) is changed according
to the magnitude of the accumulating totals of time
which was taken to repair the failure with respect to
the storage units in which the failure occurred, it is
15 possible to prevent reduction of the performance of the
processing of the normal access or read/write and limit
the time required for the data reconstruction within a
fixed period of time. Moreover, the time zone, e.g.,
the night having less processing of the normal access or
20 read/write is selected so that the system can devote
itself to the data reconstruction. As a result, it is
possible to reduce the load of the memory in the time
zone having much processing of the normal access or
read/write. Moreover, since the frequency of the data
25 reconstruction processing, or the ratio of the amount of
data reconstruction is set according to the magnitude of
the frequency of the processing of the normal access or

1 read/write, it is possible to carry out the data
reconstruction processing effectively in a time aspect.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a flow chart of the processing of
reconstructing faulty data according to the present
invention;

Fig. 2 is a block diagram showing the
arrangement of a memory according to the present
invention;

10 Fig. 3 is a diagram showing the arrangement of
a data reconstructing table for a disc at fault of the
present invention;

Fig. 4 is a flow chart showing the processing
employed in the memory of Fig. 2;

15 Fig. 5 is a flow chart of a block of selecting
the data reconstruction processing in Fig. 4;

Fig. 6 is another flow chart of a block of
selecting the data reconstruction processing in Fig. 4;

20 Fig. 7 is still another flow chart of a block
of selecting the data reconstruction processing in Fig.
4;

Fig. 8 is yet another flow chart of a block of
selecting the data reconstruction processing in Fig. 4;
and

25 Fig. 9 is a further flow chart of a block of
selecting the data reconstruction processing in Fig. 4.

09162444-092998
866260-4429160

09162444-092938

- 1 Conversely, if there is no room and the urgency of the reconstruction is high, the data reconstruction processing is given preference, and all of the normal processing such as access or read/write is cancelled or
5 ^{part} queued (Step 60). Moreover, in the case of the intermediate state in which there are some combinations between the urgency of the data reconstruction and the significance of the normal processing such as access or read/write, the data reconstruction processing
10 corresponding to the individual conditions is previously prepared in the form of programs. Then, when the conditions are changed, it can proceed to the suitable processing by replacing an old program with a new one (Step 70). Next, when the data reconstruction
15 processing is completed or interrupted, it is checked whether or not the data reconstruction processing still remains (Step 80). After all of the data reconstruction processing has been completed, the memory returns to the normal state. If the data reconstruction processing
20 still remains, the flow returns to Step 20 and the above Steps will be repeated until the data reconstruction is completed.

Next, the description will be given to a block diagram showing the arrangement of an embodiment of the
25 present invention of Fig. 2.

In Fig. 2, the reference numeral 150 designates an I/O-reconstruction control circuit which receives a command relating to I/O issued from the host

09162444.092998
866260.4429160

1 unit to carry out the processing according to the
command or respond to the host unit. Further, when the
failure is occurring in any of the storage units, the
circuit 150 serves to select a suitable data reconstruc-
5 tion method on the basis of the number of discs during
the reconstruction, the time taken to reconstruct the
faulty data, the frequency of the data reconstruction,
or the amount of the data reconstruction, and the like.
There is connected to the individual storage units a
10 monitor 155 which monitors that after the power source
for driving the storage units is activated, the driving
voltage is in a predetermined range and feeds a pseudo-
instruction for reading out the data previously stored
in a predetermined location to the storage units getting
15 into the running state to monitor the responses sent
therefrom. The reference numeral 154 designates a data
reconstructing table for the storage unit at fault of
which details will be described on referring to Fig. 3.
The reference numeral 152 designates a clock or timer
20 for obtaining the point of failure by giving the time of
day and obtaining the elapsed time during the re-
construction and the unit time by a certain method.
Then, the data reconstruction method can be changed with
the time measured by the timer as one condition. The
25 reference numeral 156 designates a circuit for re-
constructing faulty data which performs the discovery of
the faulty data, the data reconstruction and the write
of the data to a spare storage disc. Moreover, the

0916244 092993
066260" 4429160

1 circuit 156 reads out the data from all of the discs
except the disc at fault, reconstructs the faulty data
using the data thus read out, and transfers the
reconstructed data to the host unit and writes it to the
5 spare storage disc. The reference numerals 158 to 168
designate a group of data discs for storing therein the
striped data. Although the six discs are shown as the
data discs in Fig. 2, the number thereof is generally
arbitrary. The reference numerals 170 and 172 designate
10 discs which store therein the ECC data corresponding to
the striped six data which is stored in the discs 158 to
168. When the failure occurs, the faulty data is
reconstructed using the ECC data and the normal data
among the data 158 to 168. In this connection, the
15 redundancy which the memory has corresponds to the
number of ECC discs with respect to the number of discs
up to a certain number. But, in the case where the
discs break down of which number is more than that
certain number, it is impossible to reconstruct the
20 faulty data. This results in the data loss. Fig. 2
shows that even when the number of ECC data is two,
i.e., the two data discs break down, the faulty data can
be reconstructed. However, since there is generally
known the ECC production method which stands up to the
25 failure of two or more discs, the number of faulty discs
which does not result in the data loss, i.e., the
redundancy can be increased. The ECC production is
concretely realized using the Reed-Solomon Code. The

09162444-092998
866260-4429160

1 Reed-Solomon Code and the error correction method
employing the same themselves are well known. The
reference numerals 174 and 176 designate spare storage
units for storing therein the reconstructed data. Then,
5 in the case where the storage contents of the faulty
disc are stored in the spare storage unit, that spare
storage unit is accessed with the data stored therein
after the next time. The number of those discs is
generally arbitrary.

10 The description will now be given to the data
reconstructing table for the disc at fault.

The data reconstructing table 154 includes the
identification number of the spare storage disc (1), the
identification number of the disc at fault (2), the
15 point of failure (3), the sector or address of the
faulty data (4), and the flag used to judge whether or
not the failure is repairable (5).

Next, the operations of the memory of Fig. 2
and the table of Fig. 3 will be described on the basis
20 of a flow chart shown in Fig. 4.

First, in Fig. 2, it is assumed that the
failure occurs in the data disc unit 162 (Step 100).
Then, the circuit 156 for reconstructing faulty data
detects that failure to inform the I/O-reconstruction
25 control circuit 150 of that failure. After receiving
that information from the circuit 156, the circuit 150
checks whether or not an unoccupied space is present in
the data reconstructing table 154 by referring to the

09162444 092598

1 table 154 (Step 102). Subsequently, the circuit 150
checks whether or not that failure is a failure which
occurred in a new disc (Step 104). If so, the circuit
150 instructs the circuit 156 to write the following
5 initial values to the columns of interest in the data
reconstructing table 154 of Fig. 3. That is, the
circuit 156 writes the identification number SPARE 1 of
the spare disc 174 to the column of the spare storage
unit in the data reconstructing table 154, and writes
10 the identification number #2 of the data disc 162 at
fault to the column of the storage unit at fault. Next,
the circuit 156 writes the point of failure read out
from the timer 152 to the column of the point of
failure, and writes the failure occurrence address in
15 the faulty disc 162 to the column of address. Finally,
the circuit 156 initializes the reconstruction judgement
flag of each address (Step 106). If that failure is not
a new one, the processing of Step 106 is not executed,
but the processing proceeds to the subsequent Step. In
20 the subsequent Step, the circuit 150 discriminates the
state of the failure, selects either the processing of
the normal access or read/write, or the data
reconstruction processing which is suitable for the
state of the failure, and executes the selected
25 processing (Step 108). The details of this Step 108
will be described on referring to Fig. 5 to Fig. 9.
Next, when the data reconstruction processing is
completed or interrupted, it is checked whether or not

09162444-092998

1 the data reconstruction processing still remains (Step
110). When all of the data reconstruction processing is
completed, the memory returns to the normal state. When
the data reconstruction processing still remains, the
5 processing returns to Step 102, then, the above Steps
will be repeated until all of the data reconstruction
processing is completed. Even if any data reconstruc-
tion method is chosen, the circuit 156 monitors the
continuation or completion of the data reconstruction
10 processing. In the case where the subsequent failure
occurs when the data reconstruction of interest has not
yet been completed, the circuit 156 starts performing
the processing in the same manner as described above
(Step 102). Then, in the case where the number of
15 faulty discs of which data reconstruction is not
completed exceeds the redundancy of the memory, since
the data reconstruction is impossible, the circuit 150
informs the host unit of the data loss (Step 114). If
the data reconstruction processing is completed, the
20 unnecessary data in the data reconstructing table 154 is
erased and the memory returns to the normal state (Step
112). The address in the table 154 may have a track
unit, a sector unit, a word unit or any unit.

Next, the description will be given to Step
25 108 of Fig. 4 on referring to Fig. 5.

In Fig. 5, the I/O-reconstruction control
circuit 150 counts the number of discs of which data
reconstruction is not completed by referring to the data

09162444-092998
866260-44429160

1 reconstructing table 154, and compares the number of
faulty discs with the threshold (Step 120). If the
number of faulty discs is less than the threshold which
is previously set to a value less than or equal to the
5 redundancy, the circuit 150 judges that there is a room
in the redundancy, gives the processing of access or
read/write preference and performs the processing of
reconstructing faulty data within the remaining period
of time. All of the processing such as access or
10 read/write during the reconstruction waits, i.e., it is
cancelled or queued (Step 122). On the other hand, if
the number of faulty discs is more than the threshold,
the circuit 150 judges that the redundancy has no room,
gives the data reconstruction processing preference, and
15 cancels or queues all of the normal processing such as
access or read/write (Step 124).

The reconstruction is performed with a unit,
such as 1 track, in which the repair and the storage are
completed for a relatively short period of time. After
20 the completion of the reconstruction, the memory is
opened for the normal processing. But, when the
instruction of the processing of access or read/write is
issued from the host unit during the reconstruction, the
data reconstruction work is stopped immediately, and
25 then the memory is opened for the processing of access
or read/write. In the case where during the processing
of access or read/write, the data which has not yet been
reconstructed is read out, the faulty data is then

09162444-092993
866260-44429160

1 reconstructed using the ECC data and the normal data
which was used when producing the ECC data, and the
reconstructed data is sent to the host unit. At the
same time, the reconstructed data is stored in the spare
5 disc and the reconstruction judgement flag of the
address column of interest in the data reconstructing
table 154 is set to the completion of the reconstruc-
tion. If this flag is set to the completion of the
reconstruction, the subsequent access to this data is
10 performed with the spare disc. In the case of write of
data, after the ECC data has been produced, the data to
be stored in the faulty disc is stored in the spare
disc, and then the reconstruction judgement flag is set
to the completion of the reconstruction.

15 Since in the example of Fig. 2, the redundancy
is two, it is proper that the threshold is necessarily
set to 1. However, in the case where the Reed-Solomon
Code capable of correcting the multiplex dissipation
with two or more discs is used, the threshold may have
20 an arbitrary integral number less than or equal to the
redundancy. Those values are previously set in the
table 157.

 Since the I/O-reconstruction control circuit
150 stores the address of the data which was re-
25 constructed at the last time, the data reconstruction is
performed from the subsequent address. In the reconst-
ruction, the address of the data which was reconstructed
at the last time and previously stored is used. Then,

00162444-0929998

1 when the flag is not set in the data reconstructing
table 154 and thus the data reconstruction is not
completed with respect to the subsequent address, the
data of that address is reconstructed. The reconstruc-
5 tion of the data is performed in such a way that the ECC
data and the normal data which was used to produce the
ECC data from the normal discs are read out and the
circuit 156 for reconstructing faulty data is used. The
reconstructed data is written to the spare disc and the
10 flag in the data reconstructing table 154 is set to the
completion of the data reconstruction. Then, the
reconstructed data in the spare disc will be accessed.
The address of the reconstructed data is stored in the
circuit 156, and the processing by the circuit 150
15 proceeds to the subsequent data reconstruction
processing.

In the embodiment of Fig. 5, when the number
of faulty discs is less than or equal to the threshold,
the processing of the normal access or read/write takes
20 precedence over the data reconstruction. Therefore, it
is possible to reduce degradation of the performance of
access or read/write of the memory. Moreover, since in
a state in which the system devotes itself to the data
reconstruction, the reconstruction can be performed for
25 the short period of time, it is possible to maintain the
reliability of the memory.

In the above embodiments, the data reconstruction
method is selected by paying attention to only the

0916244 09298
866260 44429160

1 number of faulty discs. However, the elapsed time taken
to reconstruct the faulty data can be, in addition to
the number of faulty discs, included in the conditions.

Next, the description will be given to Step
5 108 of Fig. 4 on referring to Fig. 6.

In Fig. 6, the I/O-reconstruction control
circuit 150 counts the number of discs of which re-
construction is not yet completed by referring to the
data reconstructing table 154, and compares the number
10 of faulty discs with the threshold (Step 130). If that
number is less than or equal to the threshold, then, the
circuit 150 reads the present time from the timer 152,
and compares the time taken to reconstruct the faulty
data, which can be calculated from the present time and
15 the point of failure in the data reconstructing table
154, with a predetermined limit time (Step 132). Then,
if the reconstruction time is less than the predeter-
mined limit time, it is considered that there is a room
for the data reconstruction. Therefore, the circuit 150
20 instructs the circuit 156 for reconstructing faulty data
to give the processing of the normal access or read/
write preference, reconstruct the data in the faulty
discs within the remaining period of time, and store the
reconstructed data in the spare disc. The request to
25 perform the processing of access or read/write issued
from the host unit during the reconstruction is
cancelled or queued (Step 134). If the number of faulty
discs is more than the threshold, or the difference

09162444 092998

1 between the present time and the point of failure is
more than the predetermined limit time, it is considered
that there is no room for the data reconstruction.
Therefore, the circuit 150 cancels or queues the command
5 of the normal access or read/write issued from the host
unit and instructs the circuit 156 to give the data
reconstruction preference (Step 136).

In the embodiment of Fig. 6, when the time
taken to reconstruct the faulty data exceeds the limit
10 time, the system devotes itself to the processing of
reconstructing faulty data. Therefore, it is possible
to limit the reconstruction time within the fixed period
of time and improve the reliability of the memory.

Next, the description will be given to Step
15 108 of Fig. 4 on referring to Fig. 7.

In Fig. 7, the I/O-reconstruction control
circuit 150 obtains the present time from the timer 152
and judges whether or not that time is a time zone
having much processing of the normal access or read/
20 write (Step 140). If not, the circuit 150 cancels or
queues the command of the normal access or read/write
issued from the host unit, and instructs the circuit 156
for reconstructing faulty data to give the data re-
construction preference. Moreover, even if that time is
25 the time zone, when the number of faulty discs of Step
142 exceeds the threshold, similarly, the data re-
construction processing is given preference (Step 146).
Only when that time zone has much processing of the

1 normal access or read/write and the number of faulty
discs is less than or equal to the threshold, the
processing of the normal access or read/write is given
preference and the data reconstruction is performed for
5 the remaining period of time (Step 144).

In the embodiment of Fig. 7, when it is
previously known that the method of using the memory
depends on the time zone, the data reconstruction
processing can be assigned to the time zone having less
10 processing of access or read/write. Therefore, the data
reconstruction processing can be smoothly carried out
without the processing of access or read/write hindering
the data reconstruction processing.

In the above-mentioned embodiments of Fig. 5
15 to Fig. 7, there are provided two kinds of data recon-
struction processing in which the reconstruction or the
processing of access or read/write is given preference.
However, the kind of data reconstruction processing may
be increased in correspondence to the circumstances.

20 Next, the description will be given to Step
108 of Fig. 4 on referring to Fig. 8.

In Fig. 8, when the number of faulty discs
exceeds the threshold in Step 180, the data reconstruc-
tion processing is given preference and the processing
25 of the normal access or read/write is stopped (Step
188). When the number of faulty discs is less than or
equal to the threshold, and it is not the time zone
having much processing of the normal access or

09162441-092998
866260-11129160

0316244-092998
B66260-4429T60

1 read/write in Step 182, only the read processing is
performed and the data reconstruction processing is
given preference for the remaining period of time (Step
186). When the number of faulty discs is less than or
5 equal to the threshold and it is the time zone having
much processing of the normal access or read/write, the
processing of the normal access or read/write is given
preference and the data reconstruction processing is
performed within the remaining period of time (Step
10 184).

In the embodiment of Fig. 8, when the number
of faulty discs is less than or equal to the threshold,
but it is the time zone having less processing of the
normal access or read/write, especially, the time zone
15 having only the read processing, the read processing is
exceptionally allowed to be performed, whereby it is
possible to reduce degradation of the performance of the
memory without hindering the data reconstruction
processing.

20 Next, the description will be given to Step
108 of Fig. 4 on referring to Fig. 9.

In Fig. 9, when the number of faulty discs
exceeds the threshold in Step 190, or the number of
faulty discs is less than or equal to the threshold in
25 Step 190 and the accumulating totals of the data
reconstruction time exceeds the limit time in Step 192,
the data reconstruction processing is given preference
and the processing of the normal access or read/write is

09162444-092998
866260-4429160

1 stopped (Step 202). When the number of faulty discs is
less than or equal to the threshold and the accumulating
totals of the data reconstruction time is less than the
limit time, the I/O-reconstruction control circuit 150
5 reads the unit time from the timer 152, and compares the
frequency of the processing of the normal access or
read/write within that unit time with the predetermined
threshold (Step 194). When the frequency of the
processing of the normal access or read/write is more
10 than the threshold, it is considered that the accumu-
lation is within the limit time and there is a room for
the data reconstruction. Therefore, the processing of
the normal access or read/write is given preference and
the data reconstruction processing is performed within
15 the remaining period of time (Step 196). On the other
hand, when the frequency of the processing of the normal
access or read/write is less than the threshold, and the
frequency thereof is limitlessly near or far from the
threshold, the frequency changes in magnitude. There-
20 fore, the frequency of the data reconstruction proces-
sing or the ratio of the amount of data reconstruction
within the unit time is dynamically set according to the
magnitude of the frequency of the processing of the
normal access or read/write (Step 198). Then, the data
25 reconstruction processing is carried out according to
the frequency of the data reconstruction processing or
the ratio of the amount of the data reconstruction thus
set (Step 200).

09162444-092993

1 In the embodiment of Fig. 9, the frequency of
the data reconstruction processing or the ratio of the
amount of the data reconstruction is set according to
the magnitude of the frequency of the processing of the
5 normal access or read/write. Therefore, the data re-
construction processing will be carried out effectively
in a time aspect.

Although the magnetic disc is given as the
storage unit in the above-mentioned embodiments, the
10 present invention is not limited thereto or thereby.
That is, alternatively, an optical disc, a floppy disc,
or a semiconductor memory may be used as the storage
unit.

Moreover, as the conditions for selecting the
15 data reconstruction method, instead of the above embodi-
ments, the job contents of the host unit, the signifi-
cance of the file in the memory, and the like may be
used as the conditions. The combination of those
conditions and the data reconstruction method allows the
20 flexible data reconstruction processing to be performed.

According to the above embodiments, when the
number of storage units at fault is less than the
redundancy of the memory, the processing of access or
read/write takes precedence over the data reconstruction
25 processing. Therefore, the load of the memory is not
increased so that it is possible to reduce degradation
of the response performance of the memory in the
processing of access or read/write to the utmost.

09162444-092999

- 1 Moreover, since when a room of the redundancy becomes
small, the processing of access or read/write is
automatically stopped and the data reconstruction
processing is given preference, the reliability of the
5 memory is not reduced. Further, since the data reconst-
ruction processing method is changed according to the
accumulating totals of the data reconstruction proces-
sing time of the storage units at fault, it is possible
to realize the memory of higher reliability. Moreover,
10 since the frequency of the data reconstruction proces-
sing or the ratio of the amount of the data reconstruc-
tion is set according to the magnitude of the frequency
of the processing of access or read/write, it is
possible to carry out the data reconstruction processing
15 effectively in a time aspect.